

4. CAPACITIES AND SELECTION DATA

Duct type

75K

[illegible]

4. CAPACITIES AND SELECTION DATA

85K

[illegible]

4. CAPACITIES AND SELECTION DATA

Duct type

AUD-75UX6RZPH8

PERFORMANCE DATA (Heating Operation at Rated Frequency)																
AUD-75UX6RZPH8																
CAPACITY: 22kW INPUT: 5860 W																
INDOOR DB(°C)	OUTDOOR DB(°C)															
	-15		-10		-5		0		5		10		15		20	
	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT
10	16.50	4844	19.36	4929	23.96	5047	24.20	5190	24.46	5313	24.75	5683	25.01	5858	25.30	5978
12	15.99	4939	18.85	5036	22.77	5153	23.69	5286	23.96	5408	24.24	5766	24.51	5944	24.79	6074
14	15.49	5034	18.35	5143	20.55	5260	23.19	5382	23.45	5503	23.74	5849	24.00	6029	24.29	6170
16	14.98	5129	17.84	5246	20.04	5364	22.68	5481	22.95	5598	23.23	5937	23.50	6112	23.78	6263
18	14.48	5224	17.34	5353	19.54	5470	21.78	5577	22.00	5693	22.73	6021	22.99	6197	23.28	6358
20	13.97	5319	16.83	5459	19.03	5576	21.67	5674	21.93	5788	22.62	6105	22.48	6282	22.77	6454
22	13.46	5413	16.32	5565	18.52	5682	21.16	5770	21.43	5883	21.71	6189	22.20	6368	22.26	6550
24	12.96	5508	15.82	5671	18.02	5789	20.66	5867	20.92	5978	21.21	6273	21.47	6453	21.76	6645
26	12.45	5603	15.31	5778	17.51	5895	20.15	5963	20.42	6073	20.70	6356	20.97	6538	21.25	6741
28	11.95	5698	14.81	5884	17.01	6001	19.65	6059	19.91	6168	20.20	6440	20.46	6623	20.75	6837
30	11.44	5793	14.30	5990	16.50	6107	19.14	6156	19.40	6263	19.69	6524	19.95	6708	20.24	6933

AUD-85UX6RZPH8

PERFORMANCE DATA (Heating Operation at Rated Frequency)																
AUD-85UX6RZPH8																
CAPACITY: 25 kW INPUT: 7240 W																
INDOOR DB(°C)	OUTDOOR DB(°C)															
	-15		-10		-5		0		5		10		15		20	
	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT
10	18.75	5985	22.00	6090	27.23	6235	27.50	6412	27.80	6564	28.13	7021	28.43	7238	28.75	7386
12	18.18	6102	21.43	6222	25.88	6367	26.93	6531	27.23	6681	27.55	7124	27.85	7344	28.18	7504
14	17.60	6219	20.85	6354	23.35	6499	26.35	6650	26.65	6798	26.98	7227	27.28	7449	27.60	7623
16	17.03	6336	20.28	6482	22.78	6627	25.78	6772	26.08	6917	26.40	7336	26.70	7551	27.03	7738
18	16.45	6454	19.70	6613	22.20	6758	24.75	6891	25.00	7034	25.83	7439	26.13	7657	26.45	7856
20	15.88	6571	19.13	6744	21.63	6889	24.63	7010	24.93	7151	25.70	7543	25.55	7762	25.88	7974
22	15.30	6688	18.55	6876	21.05	7020	24.05	7129	24.35	7269	24.68	7646	25.23	7867	25.30	8092
24	14.73	6806	17.98	7007	20.48	7152	23.48	7248	23.78	7386	24.10	7750	24.40	7972	24.73	8210
26	14.15	6923	17.40	7138	19.90	7283	22.90	7367	23.20	7504	23.53	7853	23.83	8078	24.15	8329
28	13.58	7040	16.83	7270	19.33	7414	22.33	7486	22.63	7621	22.95	7957	23.25	8183	23.58	8447
30	13.00	7157	16.25	7401	18.75	7546	21.75	7606	22.05	7738	22.38	8060	22.68	8288	23.00	8565

Compact Cassette

ACT-14UR4RJCC8

PERFORMANCE DATA (Heating Operation at Rated Frequency)																
ACT-14UR4RJCC8																
CAPACITY: 4.60 kW INPUT: 1150 W																
INDOOR DB(°C)	OUTDOOR DB(°C)															
	-15		-10		-5		0		5		10		15		20	
	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT
10	3.45	951	4.05	967	5.01	990	5.06	1019	5.12	1043	5.18	1115	5.23	1150	5.29	1173
12	3.34	969	3.94	988	4.76	1011	4.95	1037	5.01	1061	5.07	1132	5.12	1166	5.18	1192
14	3.24	988	3.84	1009	4.30	1032	4.85	1056	4.90	1080	4.96	1148	5.02	1183	5.08	1211
16	3.13	1006	3.73	1030	4.19	1053	4.74	1076	4.80	1099	4.86	1165	4.91	1199	4.97	1229
18	3.03	1025	3.62	1050	4.08	1073	4.55	1095	4.60	1117	4.75	1182	4.81	1216	4.87	1248
20	2.92	1044	3.52	1071	3.98	1094	4.53	1113	4.59	1136	4.73	1198	4.70	1233	4.76	1267
22	2.82	1062	3.41	1092	3.87	1115	4.43	1132	4.48	1155	4.54	1215	4.64	1250	4.66	1285
24	2.71	1081	3.31	1113	3.77	1136	4.32	1151	4.37	1173	4.43	1231	4.49	1266	4.55	1304
26	2.60	1100	3.20	1134	3.66	1157	4.21	1170	4.27	1192	4.33	1247	4.38	1283	4.44	1323
28	2.50	1118	3.10	1155	3.56	1178	4.11	1189	4.16	1211	4.22	1264	4.28	1300	4.34	1342
30	2.39	1137	2.99	1176	3.45	1199	4.00	1208	4.06	1229	4.12	1280	4.17	1316	4.23	1360

ACT-18UR4RJCC8

PERFORMANCE DATA (Heating Operation at Rated Frequency)																
ACT-18UR4RJCC8																
CAPACITY: 5.5 kW INPUT: 1482 W																
INDOOR DB(°C)	OUTDOOR DB(°C)															
	-15		-10		-5		0		5		10		15		20	
	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT	Q	INPUT
10	4.13	1225	4.84	1247	5.99	1276	6.05	1313	6.12	1344	6.19	1437	6.25	1482	6.33	1512
12	4.00	1249	4.71	1274	5.69	1303	5.92	1337	5.99	1368	6.06	1458	6.13	1503	6.20	1536
14	3.87	1273	4.59	1301	5.14	1330	5.80	1361	5.86	1392	5.93	1479	6.00	1525	6.07	1560
16	3.75	1297	4.46	1327	5.01	1356	5.67	1386	5.74	1416	5.81	1502	5.87	1546	5.95	1584
18	3.62	1321	4.33	1354	4.88	1383	5.45	1411	5.50	1440	5.68	1523	5.75	1567	5.82	1608
20	3.49	1345	4.21	1381	4.76	1410	5.42	1435	5.48	1464	5.65	1544	5.62	1589	5.69	1632
22	3.37	1369	4.08	1407	4.63	1437	5.29	1459	5.36	1488	5.43	1565	5.55	1610	5.57	1656
24	3.24	1393	3.95	1434	4.50	1464	5.16	1484	5.23	1512	5.30	1586	5.37	1632	5.44	1681
26	3.11	1417	3.83	1461	4.38	1491	5.04	1508	5.10	1536	5.18	1608	5.24	1653	5.31	1705
28	2.99	1441	3.70	1488	4.25	1518	4.91	1532	4.98	1560	5.05	1629	5.12	1675	5.19	1729
30	2.86	1465	3.58	1515	4.13	1545	4.79	1557	4.85	1584	4.92	1650	4.99	1697	5.06	1753