RTU_15Te
Air Handling Unit for VRF Combination (Heating and Cooling)

PRODUCT SPECIFICATION SHEET

CAPACITY
- Airflow: 4500-7200 CFM
- VRF combination 12.5 to 16 tons
- Refrigerant type : R410a, R32 and R454-B available
- Tested according to AHRI 410

AIR CONDITIONING/HEATING (Standard)
- Combination DX evaporator (connection with VRF unit)
- DX evaporator connection: liquid (1/2"), gas (1 1/8")
- Economizer feature with free cooling available

AUXILIARY HEATING OPTIONS
Supplemental electric heating coil with SCR modulation (36 to 54 kW)
Indirect gas-fired furnace (300 MBH or 500 MBH)
- Indirect-fire, natural gas
- SS409 steel tube
- 10:1 modulation
- 81% efficiency
- Flame detection switches

CASING (Standard)
- Double-wall enclosure
- 22-gauge galvanized steel
- White pre-painted steel exterior finish
- Access doors with quarter-turn locks
- 18-gauge galvanized steel drain pan
- Drain connections: 1" (25 mm) NPT
- Mistop component to manage possible extra condensation
- Insulation: 2" (51 mm)
- Exhaust and supply weather hoods with bird screens
- Economizer section with motorized, airtight insulated aluminum dampers for fresh, exhaust, and mixed air.

MOUNTING
- Standard platform (Standard)
- 14-inch 18-gauge steel roof curb (Option)

product code : RC-RTU-15T-01

WARRANTY
- Components covered for 2 years
- Stainless steel exchanger covered 10 years according to OEM standard policies

COMPONENTS INSTALLED AND PRE-WIRED AT THE FACTORY
- Economizer section hood
- 36 to 54 kW electric coil with SCR modulation
- Exhaust fan and hood
- Fuse-less disconnect switch

FILTERS (Standard)
6 MERV 8 filters (16" x 20" x 2")

BLOWERS & MOTORS (Standard)
- Supply motorized impeller: 2 x 355 mm backwards inclined
- Exhaust motorized impeller: 315 mm backwards inclined
- Sealed, self-lubricating ball bearings
- High-efficiency, direct-drive EC motor

DX EVAPORATOR FROST PREVENTION/CONTROL
2 defrost options available:
- Fan speed reduction during defrost period (offtime defrost)
- Compensation by electric reheating

ELECTRICAL & CONTROLS (Standard)
- Available power supply 208V/3ph/60Hz; 460V/3ph/60Hz; 575V/3ph/60Hz
- Integrated Bacnet MSTP controller kit **product code: 699626**
- Fuse-less disconnect switch (NEMA 4)
- 24V transformer for controls
- Single point of electrical connection
- Rooftop unit with connection capabilities to Daikin, Samsung, Mitsubishi or other third-party VRFs.*

*Contact your local representative

RTU_15Te : Dimensions (Standard - Inches)





Dessus/Top



Derrière/Back | Gauche/Left | Devant/Front | Droite/Right



Dessous/Bottom

RTU_15Te : Dimensions (Standard - Inches)











Dessus/Top



Derrière/Back



Gauche/Left



Devant/Front



Droite/Right



Dessous/Bottom

RTU_15Te : Ventilation Performance



RTU_15Te : Configuration and Weight



LEGEND	
1	Fresh air intake (SA)
2	Exhaust air (EA)
3	Exhaust air return (RA)
4	Fresh air distribution (SA)

RTU WEIGHT		
Unit Weight	2444 lb	
Shipping Weight	2534 lb	
Furnace Option		
Option 1 (300 MBH)	Unit Weight	2648 lb
	Shipping Weight	2738 lb
Option 2 (500 MBH)	Unit Weight	2769 lb
	Shipping Weight	2859 lb

©2026 American ALDES Ventilation Corporation and ALDES Canada. All Rights Reserved. Reproduction or distribution, in whole or in part, of this document, in any form or by any means, without the express written consent of American ALDES Ventilation Corporation and/or ALDES Canada, is strictly prohibited. The information contained within this document is subject to change without prior written notice.